

HW Series Humanitarian Tent

HW 6m x 6m x 2.1m & HW 6m x 9m x 2.1m



Length	6 m (20 feet) and 9 m (30 feet)
Width	6 m (20 feet)
Height	2.1 m (7 feet) at eave; 11 feet at peak
Square footage	400 square feet and 600 square feet
Wind load	90mph class "C" open exposure
Roof panel	5.4 oz/ sq yd white translucent pvc fabrics
Side panel	5.4 oz/ sq yd tan exterior with white interior pvc fabrics
Visible Light	Near daylight
Windows	4 foot x 3 foot roll up window flaps
Ventilation	4 foot x 3 foot mesh window and 2- 1 foot x 1 foot gable peak vents combine to allow free flow of air through unit
Frame	1-1/2" galvanized steel frames, high strength, no rust.
Entrance/Exit	2 rollup fabric doors 2'6" x 6'8" with Velcro fasteners. Allows for breakaway exit in emergency situation (hard security door optional).
Exterior construction	One piece fabric top and fabric walls sealed using RF (radio frequency) welding to ensure a leak proof and highly durable structure. Fabrics will not rot or degrade during guarantee parameters.
UV protection	10 year UV guarantee with all units
Anchoring system	2- 3/4" x 30" steel stakes(grass or asphalt install) per tent leg with 12"x12" galvanized steel base plate. Unit can be ordered with concrete drop anchors for easy installation on concrete.
Snow Loads	Snow load kits for 10 lbs to 60 lbs are available.
Mildew Proof	Yes

Rot Proof	Yes
Cleaning Process	Washes clean with soap and water
Production capacities	150 units ready to ship 11 days after initial order. 500 units ready to ship each week 2-3 weeks after initial order.
Shipping method	75- 20x20x7 units complete per 40 foot sea container. 60- 20x30x7 units complete per 40 foot sea container. Units ship from southeastern U.S., affording an extremely low cost of transport.
Unit Weight	500 lbs – 20x20 630 lbs – 20x30
Flame Resistance	Fabrics meet or exceed NFPA 701 Registered Flame Retardant by the State of California Fire Marshall (this is the U.S. standard for flame Retardant fabric).
Installation Time	Both Humanitarian Unit sizes can be assembled by 4 installers in 45 min. complete.
Fabric Dismantled	In case of forecast hurricane or Tsunami each unit can have the complete fabrics removed in 10 min. by 4 dismantlers
Repairs & maintenance	Each unit comes with a field repair kit allowing fast and easy repairs to interior/exterior fabrics. The framework is standard size steel pipe that can be repaired or replaced in most small towns throughout the globe. Repairs will only be needed due to severe misuse.
Guarantee	Limited lifetime guarantee on frames and 10 years on fabrics.